

#230 Polypropylene Extra Heavy Duty Gloss 2.9 mil

FilmLOC® Advantage Self Wound Lamination for Labels and Tags

Description #230 extra heavy duty gloss 1.8 mil polypropylene film with 1.1 mil adhesive coating. Our thickest self wound lamination.

Applications Makes thin labels thick. More economical than using heavier face stock. Recommended for use on prime paper and film labels, including ECL (expanded content labels) labels. Reinforce or beef up thin label stocks. With #230, a 2.0 mil film stock becomes nearly 5.0 mils at a fraction of the cost of a 5.0 mil BOPP film stock. Helps labels lay flat. Thicker adhesive coating gives better wet out on semi gloss papers.

Product Data	Effective 08/14/07
<i>Film</i> PSTC-33	1.8 mil Gloss Polypropylene
<i>Adhesive</i>	1.1 mil emulsion acrylic
<i>Overall Thickness</i> PSTC-33	2.9 mil
<i>Web Width</i>	60.5" master roll
<i>Standard Length</i>	3,000' or 5,000'
<i>Availability and Shipping Location</i>	Custom slit only in Charlotte and Los Angeles.
<i>Custom Slitting Available in 1/16" Increments</i>	From 1/2" to 60.5" in 3,000' or 5,000'. Other lengths in full web cut only. There is an up charge on widths less than 2".
<i>Peel Adhesion</i> PSTC-1	24 ounces per inch
<i>Tensile Strength</i> PSTC-31	40 pounds per inch
<i>Elongation</i> PSTC-31	150% at break
<i>Application Temperatures</i>	32° F to 150° F
<i>Operating Temperatures</i>	32° F to +200° F
<i>Recommended Storage</i>	Temperature 72° F Humidity 50%
<i>Government Spec</i>	FDA spec 21CFR177-1520 for indirect food contact
<i>Quick Response</i>	Custom sizes ship in 24 hours. Orders placed before 12:00 PM eastern time generally ship the same day.
<i>Packaging</i>	Packed in cartons. Larger quantity orders available in time saving <i>Bulk Pack</i> or minimal packaging <i>Pallet Pack</i> .

IMPORTANT NOTICE TO BUYER: Replaces all prior spec sheets. All statements, information and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by, any warranty, expressed, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

FilmLOC® Division Sunbelt Sales & Marketing Associates, Inc.

170 Ottley Drive Atlanta, GA 30324
Phone 800-783-6258 or 404-892-8778
Fax 800-878-9886 or 404-874-1654

Visit our web sites www.filmloc.com or www.diamond-10.com

Sunbelt Sales is proud to be a WBENC certified Women's Business Enterprise
FilmLOC® is a registered trademark of Sunbelt Sales & Marketing Associates, Inc.