

#9615 super bond woven polypropylene repair tape

Effective 10.16.21

Description

High strength reinforced woven PP tape with an extremely aggressive adhesive. Repair tape for patching Super Sack containers, bulk bags, FIBC's, bales, woven fabric and tarps; for strapping and banding of various types of products that require extra strength; for seaming carpet backings for industrial and consumer use and for other industrial applications. Exceptional for use in applications that require extra strength and an aggressive adhesive. Easy to apply and approved for indirect food contact by FDA regulation title 21, subpart B, section 175.105. Can be sewn. Manufactured in the USA.

Applications

For patching bulk bags, FIBC's, bales, woven fabric and tarps; for strapping and banding; for seaming carpet backings; and for other industrial applications. Easy to apply. Can be sewn. Approved for indirect food contact by FDA regulation title 21, subpart B, section 175.105.

Features

Has immediate high bonding strength	Excellent long term adhesion strength
Adheres well to rough or dirty surfaces	Excellent puncture resistance

Product Data

Film	17 mil reinforced woven polypropylene fabric
Adhesive	5 mil formulated rubber adhesive
Liner	60# polysilicone paper release liner
Overall Thickness	22 mil (+/-5%)
Peel Adhesion (PSTC-101)	155 ounces per inch width
Tack (ASTM D2979)	34 ounces
Shear Strength (PSTC-107)	300 minutes
Application Temperatures	60° F to 110° F
Operating Temperatures	-4° F to 150° F
Recommended Storage	Temperature 72° F 50% humidity
Shelf Life	One year at recommended storage levels

Ordering Information

Colors	Natural
Stock Sizes	2" x 36 yd 24 rolls per case 6" x 36yd 8 rolls per case 4" x 36 yd 12 rolls per case 8" x 36 yd 4 rolls per case
Minimum Order	1 case
Custom Sizes	Other sizes available, slit to widths to 30". Minimum quantities apply.



www.filmloc.com 404.892.8778
sales@filmloc.com