

#1124 WEB SPLICING TAPE

For Non-Silicone Liners

Effective 08.17.26

DESCRIPTION

Item #1124: 2.4 mil UPVC tape with natural rubber adhesive. UPVC splicing tape for film or paper. Pliable with high adhesion.

APPLICATIONS

For splicing or tabbing film or paper substrates. Suitable for use only with uncoated substrates or surfaces.

PRODUCT DATA

Film	UPVC
Adhesive	Natural rubber adhesive
Overall Thickness	2.4 mil (+/- 5%)
Peel Adhesion	27 ounces per inch width
Tensile Strength	34 pounds per inch width
Application Temperatures	20°F to 170°F
Operating Temperatures	20°F to 170°F
Recommended Storage	Temperature 72°F; Humidity 50%
Shelf Life	Up to one year at recommended storage levels

ORDERING INFORMATION

Colors	Red, Dark Blue, Dark Green, Yellow, Orange, White
Stock Sizes	Red 1" x 72 yd - 36 rolls per case; 2" x 72 yd - 24 rolls per case
Minimum Order	1 case
Custom Sizes	Other sizes available. Minimum quantities apply.

IMPORTANT NOTICE TO BUYER

Replaces all prior spec sheets. All statements, information and recommendations herein are based on calculations and tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. Before using, user shall determine suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. Seller neither makes, nor shall be bound by, any warranty, expressed, implied, statutory or otherwise. The seller limits its obligation to replacement or, at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it. FilmLOC® is a registered trademark.

HIGH ADHESION | FILM & PAPER SPLICING | NON-SILICONE LINERS